



Material: Mosites #651-50Y
Version 1.0

Revision Date: 1-11-21

Section 1 Product and Company Identification

| | |
|-------------------------|--|
| Trade Name | Mosites #651-50Y |
| Product Group | Neoprene polychloroprene |
| Manufacturer | Mosites Rubber Company 2720 Tillar Street Fort Worth, Texas 76107 USA |
| Customer Information | Tel (817) 335-3451, Fax (817) 870-1564 www.mositesrubber.com |
| Emergency Telephone no. | (817) 335-3451 |
| Office hours: | 7:30am-5pm CST Monday-Thursday, 8am-3:30pm CST Friday |

Section 2 Hazards Identification

| | |
|--------------------------|--|
| Potential Health Effects | |
| Eyes | Dust may cause mechanical irritation with tearing, pain or visual impairment. |
| Inhalation | May cause nose, throat and lung irritation. Prolonged contact may cause chronic lung disease with altered lung function. |
| Repeated exposure | |
| Disulfiram | Liver and nervous system effects. |
| Target Organs | |
| Disulfiram | Central nervous system and liver |
| Carcinogenicity | None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen. |



Material: Mosites #651-50Y

Version 1.0

Revision Date: 1-11-21

Section 3 Composition/information on ingredients

| Component | CAS-No. | Concentration |
|------------------------------|-----------|---------------|
| Poly(2-chloro-1,3-butadiene) | 9010-98-4 | >91% |
| Rosin | 8050-09-7 | <6% |
| Disulfiram | 97-77-8 | <2% |

Section 4 First-aid Measures

| | |
|----------------|---|
| Inhalation | Remove to fresh air. Seek medical attention if irritation persists. |
| Skin Contact | Wipe away excess material then wash with soap and water. Seek medical attention if irritation persists. |
| Eye Contact | Flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists. |
| Ingestion | If victim is conscious: drink water as a precaution. Consult a physician. |
| General Advice | When symptoms persist or in all cases of doubt seek medical advice. |

Section 5 Fire-fighting Measures

| | |
|------------------------------|---|
| Flammable properties | flash point: >260°C (>500°F) open cup |
| Fire and Explosion hazards | Burning produces noxious and toxic fumes. |
| Suitable extinguishing media | Carbon dioxide (CO ₂), foam, water, dry chemical |
| Firefighting Instructions | Wear self-contained breathing apparatus and protective suit. Evacuate personal to safe areas. Do not allow run-off from fire fighting to enter drains or water courses. |



Material: Mosites #651-50Y

Version 1.0

Revision Date: 1-11-21

Section 6 Accidental Release Measures

Personal precautions

Wear proper protective gear.

Containment

Prevent material from entering drains or water courses.

Methods for clean up

Sweep up to avoid a slipping hazard while observing all environmental regulations.

Section 7 Handling and Storage

Handling

Protect from contamination. Provide appropriate exhaust ventilation to prevent dust build-up.

Wash hands immediately after handling product.

When using do not eat, drink, or smoke.

Storage

Store in a clean, dry location away from heat or flames.

Section 8 Exposure controls and personal protection

Ventilation

Mechanical ventilation in confined areas is recommended.

Personal Protective Equipment

Respiratory

not normally required with ventilation

Hand

as required by company policy

Eye

as required by company policy

Hygiene

wash with soap and water after contact

Exposure Guidelines

Exposure Limit Values

Neoprene polychloroprene

TLV (ACGIH)

10 mg/m³ TWA Inhalable particles

3mg/m³ TWA Respirable particles

Exposure Limit (OSHA)

5mg/m³ TWA Respirable fraction

15mg/m³ TWA Total dust



Material: Mosites #651-50Y
Version 1.0

Revision Date: 1-11-21

Hydrogen chloride (gas)
TLV (ACGIH) 2ppm TLV-C
Exposure Limit (OHSA) 5 ppm 7mg/m³ TLV-C

Section 9 Physical and Chemical properties

Form sheets
Color off-white, tan
Specific Gravity 1.50 g/cm³
Water solubility insoluble

Section 10 Stability and Reactivity

Conditions to avoid Processing temperatures > 200°C (>392°F). Avoid heating for prolonged periods above the upper processing limit.

Incompatibility none reasonably foreseeable

Hazardous decomposition Hydrogen chloride, Carbon monoxide, Sulphur dioxide, Organic acids, Aldehydes, Alcohols

Hazardous reactions During drying, cleaning and molding, small amounts of hazardous gases and/or particulate matter may be released that may irritate eyes, nose and throat.

Section 11 Toxicological information

Information
Poly(2-chloro-1,3-butadiene)
Oral ALD 20,000 mg/kg, rat

Rosin
Oral LD50 2,800 mg/kg, rat



Material: Mosites #651-50Y

Version 1.0

Revision Date: 1-11-21

| | |
|------------------------|--|
| Dermal LD50 | >2,000 mg/kg, rat |
| Skin irritation | non-irritant, rabbit |
| Skin sensitization | none, human |
| Repeated dose toxicity | oral, rat |
| Mutagenicity | none in animals |
| Reproductive toxicity | none in animals |
| Teratogenicity | none in animals |
| | |
| Disulfiram | |
| Dermal LD50 | >2,000 mg/kg, rabbit |
| Oral LD50 | 1,860 mg/kg, rat |
| Inhalation 4h LC50 | 3.464 mg/l, rat |
| Skin irritation | none, rabbit |
| Eye irritation | none, rabbit |
| Repeated dose toxicity | oral, dog Target organs, central nervous system and Liver |
| Carcinogenicity | none in animals |
| Mutagenicity | none in animals |
| Reproductive toxicity | none in animals |
| Teratogenicity | none in animals |

Section 12

Ecological information

Poly(2-cholo-1,3-butadiene)

This substance is not expected to produce toxic effects.

Disulfiram

48h EC50

Daphnia magna (Water flea) 0.15 mg/l

Rosin

48h EC50

Daphnia magna (Water flea) 911 mg/l

Additional information

No quantitative data exists concerning the ecological effects of this product.

Material: Mosites #651-50Y

Version 1.0

Revision Date: 1-11-21

Section 13 Disposal considerations

| | |
|--------------------|--|
| Waste Disposal | Dispose in accordance with all company and local regulations. |
| Packaging disposal | Dispose of in accordance with all company and local regulations. |

Section 14 Transport information

This product is not regulated for transport by land, sea or air. This includes: US DOT, Canada TDG Surface, IMDG-Code, and ICAO-TI/IATA-DGR.

Section 15 Regulatory information

This product contains no materials known to violate the following regulations:

EINECS
TSCA
TSCA 12 (b)
AICS
DSL
ENCS (JP)
KECI (KR)
PICCS (PH)
INV (CN)
ISHL (JP)
NZIOC
NZ HSNO
CERCLA
SARA 302 EHS
SARA 311/312
SARA 313
HAPS
RoHS



Material: Mosites #651-50Y

Version 1.0

Revision Date: 1-11-21

California proposition 65

This product contains a chemical or chemicals known to the state of California to cause cancer, birth defects and reproductive harm.

PA Right to Know

This product contains 1% or more of Rosin and Disulfiram.

NJ Right to Know

This product contains Disulfiram at a concentration of 1% or more.

Section 16

Other information

Restrictions for use

Do not use Mosites Rubber Company materials in medical applications involving implantation in the human body or in contact with internal body fluids or tissues.

The information provided in the Safety Data Sheet is correct to the best of our knowledge as of the date of publication. This SDS contains selected regulatory information and is not intended to include all regulations. It is the responsibility of the user to comply with all applicable rules, regulations, and laws relating to the use of this product.