

Material: Mosites #14272

Version 2.0 Revision Date: 3-14-23

Section 1 Product and Company Identification

Trade Name Mosites #14272

Product Group Silicone Rubber Compound Manufacturer Mosites Rubber Company

2720 Tillar Street

Fort Worth, Texas 76107

USA

Customer Information Tel (817) 335-3451, Fax (817) 870-1564

www.mositesrubber.com

Emergency Telephone no. (817) 335-3451

Office hours: 7:30am-5pm CST Monday-Thursday, 8am-3:30pm CST Friday

Section 2 Hazards Identification

Potential Health Effects

Eyes May cause eye irritation .

Inhalation May cause nose, throat and lung irritation.

Repeated exposure Vapors may have adverse effects on the

reproductive system based on animal testing of a

component of this material.

Target Organs Female reproductive system

Carcinogenicity None of the components present in this material at

concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

Section 3 Composition/information on ingredients



Material: Mosites #14272

Version 2.0 Revision Date: 3-14-23

| Туре | CAS No. | Substance | Content (wt%) |
|------------|------------|--|---------------|
| | | | |
| Ingredient | 68037-59-2 | Polydimethyl hydrogenmethyl siloxane | <= 5.0% |
| By-product | 1333-74-0 | Hydrogen gas | varies |

| Section 4 | First-aid Measures |
|----------------|---|
| Inhalation | Remove to fresh air. Seek medical attention if irritation persists. |
| Skin Contact | Wipe away excess material then wash with soap and water. Seek medical attention if irritation persists. |
| Eye Contact | Flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists. |
| Ingestion | If victim is conscious: drink water as a precaution. Consult a physician. |
| General Advice | When symptoms persist or in all cases of doubt seek medical advice. |

| Section 5 | Fire-fighting Measures |
|---|---|
| Flammable properties | not applicable |
| Fire and Explosion hazards | Burning may produce hydrogen gas, various hydrocarbon fragments, carbon dioxide, carbon monoxide, silicone dioxide, and formaldehyde. |
| Suitable extinguishing media Firefighting Instructions | Carbon dioxide (CO2), foam, water, dry chemical Wear self-contained breathing apparatus and protective suit. Evacuate personal to safe areas. Do not allow run-off from fire fighting to enter drains or water courses. |



Material: Mosites #14272

Version 2.0 Revision Date: 3-14-23

Section 6 Accidental Release Measures

Personal precautions Wear proper protective gear.

Containment Prevent material from entering drains or water

courses.

Methods for clean up Sweep up to avoid a slipping hazard while

observing all environmental regulations.

Section 7 Handling and Storage

Handling Protect from contamination. Provide appropriate

exhaust ventilation to prevent dust build-up.
Wash hands immediately after handling product.

When using do not eat, drink, or smoke.

Storage Store in a clean, dry location away from heat or

flames.

Section 8 Exposure controls and personal protection

Ventilation Mechanical ventilation in confined areas is

recommended.

Personal Protective Equipment

Respiratory not normally required with ventilation

Hand as required by company policy
Eye as required by company policy

Hygiene wash with soap and water after contact

Section 9 Physical and Chemical properties

Form sheets, or random shapes

Color black
Specific Gravity 0.86 g/cm³



Material: Mosites #14272

Version 2.0 Revision Date: 3-14-23

Water solubility insoluble

Section 10 Stability and Reactivity

Conditions to avoid Processing temperatures > 200°C (>392°F). Avoid

heating for prolonged periods above the upper

processing limit.

Incompatibility Reacts with acids, bases, alcohols, water, oxidizing

agents and catalyst to produce hydrogen gas.

Hazardous decomposition Releases flammable hydrogen gas as well as small

amounts of benzene and formaldehyde.

Hazardous reactions During drying, cleaning and molding, small

amounts of hazardous gases and/or particulate matter may be released that may irritate eyes,

nose and throat.

Section 11 Toxicological information

Information

Skin irritation none
Eye irritation none
Repeated dose toxicity none

Carcinogenicity female reproductive at 700 ppm

Mutagenicity none in animals

Reproductive toxicity minor at 500ppm and 700ppm

Teratogenicity none in animals

Section 12 Ecological information

This substance is not expected to produce toxic

effects.



Material: Mosites #14272

Version 2.0 Revision Date: 3-14-23

Section 13 Disposal considerations

Waste Disposal Dispose in accordance with all company and local

regulations.

Packaging disposal Dispose of in accordance with all company and

local regulations.

Section 14 Transport information

This product is not regulated for transport by land, sea or air. This includes: US DOT, Canada TDG Surface, IMDG-Code, and ICAO-TI/IATA-DGR.

Section 15

Regulatory information

This product contains no materials known to violate the following regulations:

EINECS

TSCA

TSCA 12 (b)

AICS

DSL

ENCS (JP)

KECI (KR)

PICCS (PH)

INV (CN)

ISHL (JP)

NZIOC

NZ HSNO

CERCLA

SARA 302 EHS

SARA 311/312

SARA 313

HAPS

RoHS

California proposition 65



Material: Mosites #14272

Version 2.0 Revision Date: 3-14-23

PA Right to Know Silica, amorphous, fumed NJ Right to Know Silica, amorphous, fumed

Section 16 Other information

Restrictions for use

Do not use Mosites Rubber Company materials in medical applications involving implantation in the human body or in contact with internal body fluids or tissues.

The information provided in the Safety Data Sheet is correct to the best of our knowledge as of the date of publication. This SDS contains selected regulatory information and is not intended to include all regulations. It is the responsibility of the user to comply with all applicable rules, regulations, and laws relating to the use of this product.