



Material: Mosites #1453  
Version 3.0

Revision Date: 3-09-23

---

Section 1 Product and Company Identification

---

Trade Name	Mosites #1453
Product Group	Silicone Rubber Compound
Manufacturer	Mosites Rubber Company 2720 Tillar Street Fort Worth, Texas 76107 USA
Customer Information	Tel (817) 335-3451, Fax (817) 870-1564 <a href="http://www.mositesrubber.com">www.mositesrubber.com</a>
Emergency Telephone no.	(817) 335-3451
Office hours:	7:30am-5pm CST Monday-Thursday, 8am-3:30pm CST Friday

---

Section 2 Hazards Identification

---

Potential Health Effects	
Eyes	May cause eye irritation .
Inhalation	May cause nose, throat and lung irritation.
Repeated exposure	Vapors may have adverse effects on the reproductive system based on animal testing of a component of this material.
Target Organs	Female reproductive system
Carcinogenicity	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

---

Section 3 Composition/information on ingredients

---



Material: Mosites #1453

Version 3.0

Revision Date: 3-09-23

Chemical Name	CAS No.	Concentration (%)
Hexamethyldisilazane reaction with Silica	68909-20-6	>30 <50

---

**Section 4** First-aid Measures

---

Inhalation	Remove to fresh air. Seek medical attention if irritation persists.
Skin Contact	Wipe away excess material then wash with soap and water. Seek medical attention if irritation persists.
Eye Contact	Flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
Ingestion	If victim is conscious: drink water as a precaution. Consult a physician.
General Advice	When symptoms persist or in all cases of doubt seek medical advice.

---

**Section 5** Fire-fighting Measures

---

Flammable properties	flash point >200 °C (>392 °F)
Fire and Explosion hazards	Ignition Temperature >400 °C (>752 °F) Burning may produce various hydrocarbon fragments, carbon dioxide, carbon monoxide, silicone dioxide, and formaldehyde.
Suitable extinguishing media	Carbon dioxide (CO <sub>2</sub> ), foam, water, dry chemical
Firefighting Instructions	Wear self-contained breathing apparatus and protective suit. Evacuate personal to safe areas. Do not allow run-off from fire fighting to enter drains or water courses.

---

**Section 6** Accidental Release Measures

---

Material: Mosites #1453

Version 3.0

Revision Date: 3-09-23

---

Personal precautions

Wear proper protective gear.

Containment

Prevent material from entering drains or water courses.

Methods for clean up

Sweep up to avoid a slipping hazard while observing all environmental regulations.

---

**Section 7****Handling and Storage**

---

Handling

Protect from contamination. Provide appropriate exhaust ventilation to prevent dust build-up.

Wash hands immediately after handling product.

When using do not eat, drink, or smoke.

Storage

Store in a clean, dry location away from heat or flames.

---

**Section 8****Exposure controls and personal protection**

---

Ventilation

Mechanical ventilation in confined areas is recommended.

Personal Protective Equipment

Respiratory

not normally required with ventilation

Hand

as required by company policy

Eye

as required by company policy

Hygiene

wash with soap and water after contact

---

**Section 9****Physical and Chemical properties**

---

Form

sheets, or random shapes

Color

opaque

Specific Gravity

1.15 g/cm<sup>3</sup>

Water solubility

insoluble

---





Material: Mosites #1453  
Version 3.0

Revision Date: 3-09-23

---

Section 13 Disposal considerations

---

Waste Disposal	Dispose in accordance with all company and local regulations.
Packaging disposal	Dispose of in accordance with all company and local regulations.

---

Section 14 Transport information

---

This product is not regulated for transport by land, sea or air. This includes: US DOT, Canada TDG Surface, IMDG-Code, and ICAO-TI/IATA-DGR.

---

Section 15 Regulatory information

---

This product contains no materials known to violate the following regulations:

EINECS  
TSCA  
TSCA 12 (b)  
AICS  
DSL  
ENCS (JP)  
KECI (KR)  
PICCS (PH)  
INV (CN)  
ISHL (JP)  
NZIOC  
NZ HSNO  
CERCLA  
SARA 302 EHS  
SARA 311/312  
SARA 313  
HAPS

Material: Mosites #1453

Version 3.0

Revision Date: 3-09-23

---

RoHS

California proposition 65

PA Right to Know

dimethyl Siloxane, Dimethylvinylsiloxyl  
Hexamethyldisilazane reaction with silica  
dimethyl siloxane, Dimethylvinylsiloxyl  
Hexamethyldisilazane reaction with silica  
Dimethyl, methylvinyl siloxane,  
dimethylvinyl-  
Dimethylcyclosiloxanes

NJ Right to Know

---

Section 16

Other information

---

Restrictions for use

Do not use Mosites Rubber Company materials in medical applications involving implantation in the human body or in contact with internal body fluids or tissues.

The information provided in the Safety Data Sheet is correct to the best of our knowledge as of the date of publication. This SDS contains selected regulatory information and is not intended to include all regulations. It is the responsibility of the user to comply with all applicable rules, regulations, and laws relating to the use of this product.