

Trade Name	Mosites #651-90
Product Group	Neoprene polychloroprene
Manufacturer	Mosites Rubber Company
	2720 Tillar Street
	Fort Worth, Texas 76107
	USA
Customer Information	Tel (817) 335-3451, Fax (817) 870-1564
	www.mositesrubber.com
Emergency Telephone no.	(817) 335-3451
Office hours: 7:30am-5pm CST Monday-	Thursday, 8am-3:30pm CST Friday

Section 2	Hazards Identification
Potential Health Effects	
Eyes	Dust may cause mechanical irritation with tearing, pain or visual impairment.
Inhalation	May cause nose, throat and lung irritation. Prolonged contact may cause chronic lung disease with altered lung function.
Repeated exposure Disulfiram	Liver and nervous system effects.
Target Organs Disulfiram Carcinogenicity	Central nervous system and liver
caremogenicity	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.



Revision Date: 3-14-23



Material: Mosites #651-90

Version 1.0

Revision Date: 3-14-23

Section 3 Composition/information on ingredients

Component	CAS-No.	Concentration
Poly(2-chloro-1,3-butadiene	9010-98-4	>91%
Rosin	8050-09-7	<6%
Disulfiram	97-77-8	<2%

Section 4	First-aid Measures
Inhalation	Remove to fresh air. Seek medical attention if irritation persists.
Skin Contact	Wipe away excess material then wash with soap and water. Seek medical attention if irritation persists.
Eye Contact	Flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
Ingestion	If victim is conscious: drink water as a precaution. Consult a physician.
General Advice	When symptoms persist or in all cases of doubt seek medical advice.
Section 5	Fire-fighting Measures

Flammable properties Fire and Explosion hazards Suitable extinguishing media Firefighting Instructions flash point: >260°C (>500°F) open cup Burning produces noxious and toxic fumes. Carbon dioxide (CO2), foam, water, dry chemical Wear self-contained breathing apparatus and protective suit. Evacuate personal to safe areas. Do not allow run-off from fire fighting to enter drains or water courses.



Material: Mosites #651-90 Version 1.0	Revision Date: 3-14-23
Section 6 Accide	ntal Release Measures
Personal precautions Containment	Wear proper protective gear. Prevent material from entering drains or water courses.
Methods for clean up	Sweep up to avoid a slipping hazard while observing all environmental regulations.
Section 7 Handlin	ng and Storage
Handling	Protect from contamination. Provide appropriate exhaust ventilation to prevent dust build-up. Wash hands immediately after handling product. When using do not eat, drink, or smoke.
Storage	Store in a clean, dry location away from heat or flames.
Section 8 Exposu	ire controls and personal protection
Section 8 Exposu Ventilation	re controls and personal protection Mechanical ventilation in confined areas is recommended.
Ventilation Personal Protective Equipment	Mechanical ventilation in confined areas is recommended.
Ventilation Personal Protective Equipment Respiratory	Mechanical ventilation in confined areas is recommended. not normally required with ventilation
Ventilation Personal Protective Equipment Respiratory Hand	Mechanical ventilation in confined areas is recommended. not normally required with ventilation as required by company policy
Ventilation Personal Protective Equipment Respiratory Hand Eye	Mechanical ventilation in confined areas is recommended. not normally required with ventilation as required by company policy as required by company policy
Ventilation Personal Protective Equipment Respiratory Hand	Mechanical ventilation in confined areas is recommended. not normally required with ventilation as required by company policy
Ventilation Personal Protective Equipment Respiratory Hand Eye Hygiene Exposure Guidelines Exposure Limit Values	Mechanical ventilation in confined areas is recommended. not normally required with ventilation as required by company policy as required by company policy
Ventilation Personal Protective Equipment Respiratory Hand Eye Hygiene Exposure Guidelines	Mechanical ventilation in confined areas is recommended. not normally required with ventilation as required by company policy as required by company policy wash with soap and water after contact



Material: Mosites #651-90 Version 1.0

Revision Date: 3-14-23

Hydrogen chloride (gas) TLV (ACGIH) Exposure Limit (OHSA)

2ppm TLV-C 5 ppm 7mg/m³ TLV-C

Section 9	Physical and Chemical properties	
Form	sheets	
Color	off-white, tan	
Specific Gravity	1.57 g/cm ³	
Water solubility	insoluble	
Section 10	Stability and Reactivity	
Conditions to avoid	Processing temperatures > 200°C (>392°F). Avoid heating for prolonged periods above the upper processing limit.	
Incompatibility	none reasonably foreseeable	
Hazardous decomposition	Hydrogen chloride, Carbon monoxide, Sulphur dioxide, Organic acids, Aldehydes, Alcohols	
Hazardous reactions	During drying, cleaning and molding, small amounts of hazardous gases and/or particulate matter may be released that may irritate eyes, nose and throat.	
Section 11 Toxicological information		
Information		
Poly(2-chloro-1,3-butadien	e)	
Oral ALD	20,000 mg/kg, rat	
Rosin		



Material: Mosites #651-90 Version 1.0 Revision Date: 3-14-23 Dermal LD50 >2,000 mg/kg, rat Skin irritation non-irritant, rabbit none, human Skin sensitization Repeated dose toxicity oral, rat Mutagenicity none in animals **Reproductive toxicity** none in animals Teratogenicity none in animals Disulfiram Dermal LD50 >2,000 mg/kg, rabbit Oral LD50 1,860 mg/kg, rat Inhalation 4h LC50 3.464 mg/l, rat Skin irritation none, rabbit Eye irritation none, rabbit Repeated dose toxicity oral, dog Target organs, central nervous system and Liver Carcinogenicity none in animals Mutagenicity none in animals **Reproductive toxicity** none in animals Teratogenicity none in animals Section 12

Disulfiram 48h EC50 Rosin 48h EC50

Ecological information

Poly(2-cholo-1,3-butadiene)

Additional information

This substance is not expected to produce toxic effects.
Daphnia magna (Water flea) 0.15 mg/l

Daphnia magna (Water flea) 911 mg/l No quantitative data exists concerning the ecological effects of this product.

5 of 7



Material: Mosites #651-90

Version 1.0

Revision Date: 3-14-23

Section 13	Disposal considerations
Waste Disposal	Dispose in accordance with all company and local regulations.
Packaging disposal	Dispose of in accordance with all company and local regulations.
Section 14	Transport information

This product is not regulated for transport by land, sea or air. This includes: US DOT, Canada TDG Surface, IMDG-Code, and ICAO-TI/IATA-DGR.

Section 15	Regulatory information	

This product contains no materials known to violate the following regulations: EINECS TSCA TSCA 12 (b) AICS DSL ENCS (JP) KECI (KR) PICCS (PH) INV (CN) ISHL (JP) NZIOC NZ HSNO CERCLA SARA 302 EHS SARA 311/312 SARA 313 HAPS POHS
RoHS



Material: Mosites #651-90 Version 1.0	Revision Date: 3-14-23	
California proposition 65	This product contains a chemical or chemicals known to the state of California to cause cancer, birth defects and reproductive harm.	
PA Right to Know	This product contains 1% or more of Rosin and Disulfiram.	
NJ Right to Know	This product contains Disulfiram at a concentration of 1% or more.	
Section 16 Other information		

Restrictions for use

Do not use Mosites Rubber Company materials in medical applications involving implantation in the human body or in contact with internal body fluids or tissues.

The information provided in the Safety Data Sheet is correct to the best of our knowledge as of the date of publication. This SDS contains selected regulatory information and is not intended to include all regulations. It is the responsibility of the user to comply with all applicable rules, regulations, and laws relating to the use of this product.